

DivoEco®UD3

| № | Property, unit | Value | | | | | | | Test standard | Tolerance |
|---|--|---------|------|------|---------|--------------|------|----------------------|------------------|-----------|
| | | 170 | 215 | 260 | 290 | without glue | | | | |
| | | | | | | 320 | 340 | 410 | | |
| 1 | Grammage, gsm | 170 | 215 | 260 | 290 | 320 | 340 | 410 | DSTU 2297 | ±3% |
| 2 | Thickness, µm | 220 | 290 | 350 | 395 | 445 | 470 | 580 | DSTU EN 20534 | ±5% |
| 3 | Stiffness L&W (5°), mNm: - CD - MD | - | 2.9 | 5.5 | 7.8 | 10.2 | 12.6 | 21.4 | DIN 53121 | ±15% |
| | | - | 12.5 | 21.1 | 29.6 | 37.7 | 44.2 | 67.9 | | |
| 4 | Surface water absorption (COBB ₆₀), gsm: - Top; - Bottom | max 50 | | | min 100 | | | DSTU 3549 ISO 535 | | |
| | | max 100 | | | | | | | | |
| 5 | Brightness Top, %, min | 46 | | | | | | | DSTU ISO 2470 | |

Laboratory test climate: (23±1) °C, (50±2) %.
Issued: 01.02.2020.
All figures mentioned above may be subject to technical changes.

Packaging

| | | | |
|-------|--------------------|---|------------|
| Sheet | width: | max 1580 mm | min 470 mm |
| | length: | max 1580 mm | min 520 mm |
| | bale height: | max 1400 mm | min 800 mm |
| | type of packaging: | shrink film, bale on the pallet with the busbar | |

| | | | |
|------|--------------------|-------------|------------|
| Reel | width: | max 2500 mm | min 500 mm |
| | diameter: | max 1400 mm | min 950 mm |
| | type of packaging: | paper | |
| | core: | 150 mm | |