

DivoPack®UD1

№	Property, unit	Value						Test standard	Tolerance
		170	220	250	310	without glue			
						350	410		
1	Grammage, gsm	170	220	250	310	350	410	DSTU 2297	±3%
2	Thickness, µm	220	290	340	420	450	580	DSTU EN 20534	±5%
3	Stiffness L&W (5°), mNm: - CD - MD	- -	3.2 13.8	4.4 18.6	9.8 34.3	14.5 50.6	22.3 73.7	DIN 53121	±15%
4	Surface water absorption (COBB ₉₀), gsm: - Top; - Bottom				max 50 max 100		min 100	DSTU 3549 ISO 535	
5	Brightness Top, %, min				76			DSTU ISO 2470-2	

Laboratory test climate: (23±1) °C, (50±2) %.
 Issued: 01.12.2019.
 All figures mentioned above may be subject to technical changes.

Packaging

Sheet	width:	max 1580 mm	min 470 mm
	length:	max 1580 mm	min 520 mm
	bale height:	max 1400 mm	min 800 mm
	type of packaging:	shrink film, bale on the pallet with the busbar	

Reel	width:	max 2500 mm	min 500 mm
	diameter:	max 1400 mm	min 950 mm
	type of packaging:	paper	
	core:	150 mm	